KD-H Slide Dryer (New model)



Features:

🗁 Touch operating system: touch-type high-definition LED digital display, equipped with heating status indicator light.

🗁 Smart split combination: the water bath, floatation workstation , and slide dryer machines are independent and can be combined, and can be combined online to save power ports.

🗁 Intelligent PID temperature control: equipped with double high-precision temperature sensors.

🗁 Multiple temperature control protection: multiple temperature measurement, uniform and constant temperature control, intelligent temperature control.

🗁 Separate water bath dish: The separate water bath dish and the separate drying table are interchangeable, making replacement easy.

🗁 Multi-functional drying table: The drying tank is equipped with a temperature measurement, draining and drying platform. Drain the liquid first and then dryer the slices. The tissue is not easy to slide down and prevents blistering of the slices.

🗁 Sealing wax on the drying table: Equipped with a sealing wax tank, the tissue wax block is sealed and protected when the sectioning is completed, reducing the number of processes.

Technical Specifications:

- Dimensions of drying station: 256x188x52mm(W×D×H)
- Capacity of drying station:100 slides (10 rows, 10 slides in each row)
- Dimensions of wax sealing stand:74x46x5mm(W×D×H)
- Temperature setting range:0~99℃
- Drying table slope angle: 60°
- Working Voltage: AC 100V~120V/AC 220V~240V
- Power frequency:50Hz/60Hz
- Power: 350W
- Dimensions:330x375x130mm
- Net weight:6 kg